



**RELIABLE SCALE CORPORATION**  
520 Moraine Road NE  
Calgary, Alberta, Canada T2A 2P2  
TELEPHONE: (403) 272-8784  
TOLL FREE: (800) 419-1189  
FAX: (403) 273-9818  
E-mail: [info@reliablescale.com](mailto:info@reliablescale.com)  
Web: [www.reliablescale.com](http://www.reliablescale.com)

Live Animal Weighing

January 4, 2008

Cattle-Logger™

RE: Reliable Scale Model 565 Digital Weight Indicator

Automatic Sorting

A flaw in the internal Real Time Clock (time of day) processing may cause the Model 565 to lock up or automatically turn off after power up.

Poultry Growth Monitors

The internal roll-over from 2007 to 2008 may cause the internal date to become corrupted and set an invalid year in the Real Time Clock. The lock up/automatic power off manifests itself when the Model 565 is in an alarm condition at startup. When the alarm condition is logged to internal memory while the date in the Real Time Clock is invalid, the flaw can occur. The power must be removed from the Model 565 before it can be restarted.

Feed Mixer Scales

Pen & Platform Scales

Custom Load Cells & Pins

Load Cell Repairs

Logging of alarm conditions was added at firmware version 1.48.11. The firmware version number is displayed at power on. The default alarm logging conditions are weights under 1000 lb and over 5000 lb.

All Weather Weight Indicators

Pump Jack Load Cells

Model 565 and Model 565D indicators produced or upgraded to new firmware after February 29, 2004 may be affected

Mobile Weighing Systems

If the Model 565 is not in alarm condition or alarm logging is disabled, the flaw will not manifest itself and the internal date can be reset ensuring normal operation of the Model 565.

Wireline Load Sensors

R&D Projects

Correction of this condition can be done simply in the field.

Data Loggers

Rentals